



Ockwells Standard Gaffer Tape

Properties	Unit	Value
Total thickness	mm	0.17 ± 5.00%
Adhesive	-	Rubber
Mesh Number	Mesh	25
Rolling Ball Tack	Ball	10
Peel adhesion 180°	KG/cm	3.2
Tensile strength	N/10mm	≥ 28
Service temperature	°C	-15 ~ +60
Storage temperature	°C	Normal room temp.
Shelf life	Month	24

1. The data above is typical and subject to change without notice
2. The product should be stored at room temperature and kept from moisture and heat source
3. It is essential as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry and free of grease and oil.
4. Dimension Tolerance Gaffer Tapes:
Thick: ±0.02mm for thickness up to and including 0.20mm, ±0.03mm for greater thickness
Width: ±1mm for widths up to and including 19mm, ±1.5mm for greater widths
Length: ±30cm for lengths up to and including 25m, ±50cm for greater lengths within 100m.

Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area in order to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk